

## Technische Daten / Technical Data

### Model M3 355M4-4

Housing material		Casting iron
Phase		Three
Frame size		355
Power(50Hz)	kW	400.00
Current(A)400V	Δ	675.72
Current(A)690V	Y	391.72
Speed(50Hz)	(r/min)	1490
Efficiency	IE3	
	Eff.100%	96.00
	Eff.75%	96.30
	Eff.50%	95.50
Power factor cosφ	100% load	0.89
60Hz 460/793V	Power(kW)	460.00
60Hz 480/830V	Power(kW)	480.00
Speed(60Hz)	(r/min)	1788
Regulations		IEC / DIN / ISO / VDE / EN
Standard		IEC 60034
Ambient Temp.		-20°C ~ +40°C

Rated torque(N.m)	2564.87
Tst/Tn (Times)	2
Tmax/Tn (Times)	2.3
Tmin/Tn (Times)	1.3
Ist/In (Times)	7.5
Bearings type(DE)	NU322
Bearings type(NDE)	6322C3
Oil seals	110*130*12
Cable glands	2-M63*1.5
Insulation class	F
Protection degree	IP 55
Thermal protection	3*PTC
Rotation direction	Clockwise
Service duty	S1
Balance	Half-key balanced
Cooling	IC 411
Noise dB(A)	95
Maximum altitute	1000 m above sea level